

# MATERIAL SAFETY DATA SHEET

Emergency Response: 1800 033 111  
Sipcam Pacific Australia Pty Ltd ACN 073 176 888  
Suite 11/23-31 Gheringhap St  
Geelong, Victoria, 3220 AUSTRALIA

Phone: (03)5223 3746  
Fax (03)5223 3756

Not classified as hazardous according to the criteria of NOHSC Australia.

## I IDENTIFICATION

Product Name: Sipcam Fluocam 500 Herbicide

Other Names: None.

Product Code: None.

UN No: None allocated

Hazchem Code: None allocated

Dangerous Goods Class: None allocated

Sub Risk Class: None allocated

Packaging Group: None allocated

Poison Schedule: Not scheduled.

Chemical Family: Water solution of ingredients (see below). Active ingredient is a urea derived herbicide.

Uses: Herbicide for use as described on product label.

## Physical Appearance & Properties

Appearance & Odour: Off-white suspension. Almost odourless.

Melting/softening point: Approximately 0°C.

Boiling point and vapour pressure: Approximately 100°C at 100kPa.

Volatile materials: Water component.

Flashpoint: Does not burn.

Flammability limits: Not applicable. This product does not burn.

Specific gravity: Not available.

Solubility in water: Completely soluble.

Corrosiveness: Not corrosive.

Vapour Pressure: 18mm Hg at 20°C (water vapour pressure).

Ingredients	Chemical Entity	CAS No	Proportion, %	Worksafe Exposure Limits	
				TWA, mg/m <sup>3</sup>	STEL, mg/m <sup>3</sup>
	fluometuron	2164-17-2	50	not set	not set
	ethylene glycol	107-21-1	5-10	60	120
	Other non hazardous ingredients	secret	<10	not set	not set
	Water	7732-18-5	to 100	not set	not set

This is a commercial product whose exact ratio of components may vary. Trace quantities of impurities are also likely.

## II HEALTH HAZARD DATA

### Health Effects:

No specific data is available for the product for chronic exposure symptoms. The ingredients are not listed as carcinogenic in Worksafe's document "Exposure Standards for Atmospheric Contaminants in the Occupational Environment" (May 1995), nor in NOHSC's "List of Designated Hazardous Substances" (April 1999).

### Acute Effects:

Swallowed: Single dose oral toxicity is considered to be low. No hazards are anticipated from swallowing small amounts incidental to normal handling operations.

Eye: This product is mildly irritating to the eyes. It is likely to cause mild discomfort such as watering and redness of the eyes. However, this should quickly disappear once exposure is over.

Skin: This product is mildly irritating to skin. However, it is unlikely to cause more than minor discomfort or effects such as itchiness, occasional small blisters or slight skin reddening.

Inhalation: No inhalation hazards incidental to normal handling operations are anticipated from this product when used at room temperatures.

For fluometuron:

LD<sub>50</sub> Oral (Rat) >6000mg/kg

LD<sub>50</sub> Dermal (Rat) >2000mg/kg

# MATERIAL SAFETY DATA SHEET

LD<sub>50</sub> Dermal (Rabbit) >10,000mg/kg

## First Aid:

If poisoning occurs, contact a Doctor or Poisons Information Centre. Phone 13 1126 from anywhere in Australia. If possible have this MSDS or product label with you.

Swallowed: If swallowed, do NOT induce vomiting. Wash mouth with water and give a glass of water to drink.

Eyes: If product gets in eyes, wash material from them with running water. If they begin watering or reddening, take special care in washing thoroughly.

Skin: If product gets on skin, thoroughly wash contacted areas. No further measures should normally be required unless irritation is noticed. If irritation persists, seek medical attention.

Inhalation: No first aid measures normally required. However, if vapours or mists have been inhaled, and irritation has developed, remove to fresh air and observe until recovered. If irritation becomes painful or persists more than about 30 minutes, seek medical advice.

Advice to Doctor: Treat symptomatically. Note the nature of this product.

---

## III PRECAUTIONS FOR USE

### Exposure Standards:

A time weighted average (TWA) has been established for ethylene glycol, present in significant quantities in this product. This value is 60mg/m<sup>3</sup>. The corresponding STEL level is 120mg/m<sup>3</sup>. The STEL (Short Term Exposure Limit) is an exposure value that should not be exceeded for more than 15 minutes and should not be repeated for more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The exposure value at the TWA is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. See ingredients section on page 1 of this data sheet. The ADI (Acceptable Daily Intake) for fluometuron is set at 0.02mg/kg/day. The corresponding NOEL (No-observable-effect-level) is set at 2mg/kg/day. Values taken from Australian ADI List, January 2001.

### Engineering Controls:

In industrial situations, concentration values below the TWA value should be maintained. Values may be reduced by process modification, use of local exhaust ventilation, capturing substances at the source, or other methods. If you believe air borne concentrations of mists, dusts or vapours are high, you are advised to modify the process or environment to reduce the problem.

### Personal Protection:

Respiratory Protection: It is usually safe to not use a dust mask or respirator protection on account of this product. However, if the product is being used in dusty or confined conditions, use of a mask or respirator may be preferred. For help in selecting suitable equipment, consult AS/NZS 1715.

Protective Gloves: Impermeable protective gloves should be worn when you are using this product, to prevent irritation. For help in selecting suitable equipment, consult AS 2161.

Eye Protection: Protective eyewear is suggested when using this product. It is always prudent to use protective eyewear. Consult AS1336 and AS/NZS 1337 for advice on Industrial Eye Protection.

Clothing: Clean overalls or protective clothing should be worn, preferably with an apron. Consult AS2919 for advice on Industrial Clothing.

Safety Boots: Wearing safety boots in industrial situations is advisory. Consult AS/NZS2210 for advice on Occupational Protective Footwear.

Always wash hands before smoking, eating or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

---

## IV SAFE HANDLING INFORMATION

### Storage & Transport

No special storage and transport requirements. This product has no UN classification. Not a Scheduled Poison. Containers should be kept closed in order to minimise contamination. Keep from extreme heat and open flames, and make sure that the product does not come into contact with substances listed under "Materials to avoid" below.

### Spills & Disposals

Minor spills do not normally need any special cleanup measures. In the event of a major spill, prevent spillage from entering drains or water courses. As a minimum, wear overalls, goggles and gloves. Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. Sweep up and shovel or collect recoverable product into labeled containers for recycling or salvage, and dispose of promptly. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. Full details regarding disposal of used containers, spillage and unused material may be found on the label. If there is

# MATERIAL SAFETY DATA SHEET

any conflict between this MSDS and the label, instructions on the label prevail. Dispose of only in accord with all regulations.

## Fire & Explosion Hazard

There is no risk of an explosion from this product under normal circumstances if it is involved in a fire.

Flashpoint: Does not burn.

Flammability limits: Not applicable. This product does not burn.

Extinguishing Media: This product does not burn. Use extinguishing media suited to the materials that are burning.

Special Fire Fighting procedures: When fighting fires involving significant quantities of this product, wear safety boots, non-flammable overalls, gloves, hat, goggles and respirator. All skin areas should be covered.

Unusual Fire & Explosion Hazards: Fire decomposition products from this product may form toxic and corrosive mixtures in confined spaces. Likely to decompose only after heating to dryness followed by further strong heating.

Stability: This product is unlikely to spontaneously decompose.

Polymerisation: This product is unlikely to spontaneously polymerise.

Decomposition Products: Carbon dioxide, and if combustion is incomplete, carbon monoxide and smoke. Nitrogen and its compounds, and under some circumstances, oxides of nitrogen. Hydrogen fluoride gas and fluorides. Water.

Materials to avoid: No particular incompatibilities.

---

## V OTHER INFORMATION

This MSDS is prepared in accord with the Worksafe Australia document "National Code of Practice for the Preparation of Material Safety Data Sheets", 1994.

### Contact Points:

**Police and Fire Brigade:**

**Dial**

**AUSTRALIA**

**000**

**If ineffective:**

**Dial**

**1100 (Exchange)**

**For emergency response:**

**Dial**

**1800 033 111**

**National Poisons Information Centre:**

**Dial 13 1126 (from anywhere in Australia)**

**Please read all labels carefully before using product.**

This MSDS summarises our best knowledge of the health and safety hazard information of the product and how to safely handle and use the product in the workplace. Each user should read this MSDS and consider the information in the context of how the product will be handled and used in the workplace including in conjunction with other products. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact this company. The responsibility for products sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available on request.

This MSDS copyright © Kilford & Kilford Pty Ltd, September, 2001.

<http://www.kilford.com.au> Phone (02)9516 2079